

Pile Dynamics 17-May-12 14:16 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s JC 0.40 FM 1.00 VM 1.00 EA/C 30.3 Ks/ft UN KIPS 0.1 FR 20000 MB 30 DL -27 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1030	FS — BN 778 10 SL 3239/ 3440/ 99 PJ: sn PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 B PD: 40637-075 LP 0.00 ft TB 8.0 TI 9.6 2L/C 4.7 UA 1000 UE 1022 LI 1.0
---	--

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 4.0 FMX= 61 AMX= 169
 EMX= 0.2 MEX= 119 FUP= 1.00



contact File Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 40637
 CALIBRATION FACTOR: 1030 G/v
 PAK (*5000): DATE: 17-MAY-12
 PDA OPERATOR: *[Signature]*