

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 05-Mar-15 03:56	FS — 10	BN 1000 SL 684/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB 30 DL -30 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1175	TS 12 TB 8.0	B PD: 43781-075 T1 9.5 2L/C 4.7 VA 1000 UE 1022	LP 0.00 ft LI 1.0	

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 4.1 FMX= 65 AMX= 129
 EMX= 0.2 MEX= 127 FUP= 1.00

contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 43781 PE

CALIBRATION FACTOR: 1175 G/V

PAK ←58007? DATE: 5-MAR-15

PDA OPERATOR: [Signature]

←-AT:PIEZORESISTIVE OP: dale [ver:4.05] [AT:PIEZOELECTRIC-]