


<b>Pile Dynamics</b> 01-May-13 07:32 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s  JC 0.40 FM 1.00 UM 1.00  EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30  DL -37 UT -1 PK 1 TM-PEAK  F1 500 F2 213 A1 999 A2 1115	FS — BN 625 PJ: sn 10 SL 84/ 3440/ 99 PN: HOPBAR  TG F2 -- US A2 F2 3.3  TS 12 B PD: 43806-075 LP 0.00 ft TB 8.0 T1 9.4 2L/C 4.7 UA 1000 UE 1022 LI 1.0
--	--

<b>ACCEPT SQ-OFF FL-OFF PR-OFF</b>  contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	VMX= 3.9 FMX= 61 AMX= 149 EMX= 0.2 MEX= 119 FUP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 43806 CALIBRATION FACTOR: 1115 G/V PAK (*5000): DATE: 01-MAY-13 PDA OPERATOR: <i>Alex</i> ←-AT:PIEZORESISTIVE OP: alex [ver:4.05] AT:PIEZOELECTRIC->
---	---