


QBTA: ON IALT-F1/BB=601

Pile Dynamics, Inc.

DPF

File Dynamics 16-Apr-13 13:57	FS — 10	BN 892 SL 89/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB 30				
DL -42 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1135				
TS 12 B PD: 43808-075 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 VA 1000 UE 1022 LI 1.0				

ACCEPT SQ-OFF FL-OFF PR-OFF	UMX= 4.1 FMX= 64 AMX= 149 EMX= 0.3 MEX= 125 FUP= 1.00
-----------------------------	--


 contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 43808
 CALIBRATION FACTOR: 1135 G/v
 PAK (*5000): DATE: 16-APR-13
 PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->