

QBTA: ON IALT-F1/BB=601

Pile Dynamics, Inc.

DPF

Pile Dynamics 16-Apr-13 14:13		FS — BN 944 10 SL 90/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30				
DL -41 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1110				
TS 12 TB 8.0		B PD: 43810-075 LP 0.00 ft T1 9.4 2L/C 4.7 UA 1000 UE 1022 LI 1.0		

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 4.0 FMX= 61 AMX= 139
 FMX= 0.2 MEX= 119 FVP= 1.01



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 43810

CALIBRATION FACTOR: 1110 G/v

-PAK (<X5000>): DATE: 16-APR-13

PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: alex Iver:4.051

AT:PIEZOELECTRIC->