


QBTA: ON IALT-F1/BB=601

Pile Dynamics, Inc.

DPF

File Dynamics 01-May-13 07:42 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -34 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1130	FS — BN 651 PJ: sn 10 SL 84/ 3440/ 99 PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 B PD: 43811-075 LP 0.00 ft TB 8.0 T1 9.4 2L/C 4.7 UA 1000 UE 1022 LI 1.0
---	--

ACCEPT SQ-OFF FL-OFF PR-OFF  contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	VMX= 4.0 FMX= 62 AMX= 149 EMX= 0.2 MEX= 121 FUP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 43811 CALIBRATION FACTOR: 1130 G/v PAK (*5000) DATE: 01-MAY-13 PDA OPERATOR: <i>[Signature]</i> OP: alex [ver:4.051]
---	--

<-AT:PIEZORESISTIVE

AT:PIEZOELECTRIC->