

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics  
2018-02-22 11:48

FS — BN 619  
10 SL 644/ 3440/ 99

PJ:  
PN: HOPBAR

TG F2 -- US  
A2 F2 3.3

LE 17.0 ft  
AR 1.7 in2  
EM 30000 Ksi  
SP 0.492 K/ft3  
WS 16810 ft/s  
WC 7312 ft/s

JC 0.40  
FM 1.00  
UM 1.00

EA/C 30.3 Ks/ft  
UN KIPS\*0.1  
FR 20000 MB 90

DL -44  
UT -1 IP 0.00  
PK 1 TM-PEAK

F1 500  
F2 213  
A1 220  
A2 1225

TS 12 B PD: 45609-075 LP 0.00 ft  
TB 8.0 T1 9.5 2L/C 4.7 VA 1000 UE 1024 LI 1.0

UMX= 4.2 FMX= 66 AMX= 129  
EMX= 0.3 MEX= 129 FUP= 1.00

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT



ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 45609

CALIBRATION FACTOR: 1225 G/V

PAK (\*5000): DATE: 22 FEB 18

PDA OPERATOR: [Signature]

<-AT:PIEZORESISTIVE

OP: laine [ver:5.01]

AT:PIEZOELECTRIC->