


QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

File Dynamics 16-Apr-14 08:06 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS 0.1 FR 20000 MB 30 DL -42 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1130	FS — BN 1398 10 SL 386/ 3440/ 99 PJ: PN: HOPBAR TG F2 -- US A2 F2 3.3
--	--

TS 12	T1 9.3	B PD: 47556-075	LP 0.00 ft
TB 8.0	2L/C 4.7	UA 1000	LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF  contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	VMX= 4.0 FMX= 62 AMX= 129 EMX= 0.3 MEX= 121 FUP= 1.01 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 47556 CALIBRATION FACTOR: 1130 G/v PAIR (*5000): DATE: 16-Apr-14 PDA OPERATOR: Erik Sverdrup OP: erik [ver:4.054]
--	--

Smart Sensor

Smart Chip Programmed By E.S. on 4-16-14 CRC Value F99E