


QBTA: ON [ALT-F1/BB=60]

File Dynamics, Inc.

File Dynamics
2015-05-06 06:00FS — BN 127
10 SL 518/ 3440/ 2PJ:
PN: HOPBARTG F2 DPF
A 4 -- US
F 2 3.3LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16810 ft/s
WC 17032 ft/sJC 0.40
FM 1.00
UM 1.00EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 30DL -43
UT -1 IP 0.00
PK 1 TM-PEAKF1/2 500/ 213
F3/4 213/ 213
A1/2 999/ 999
A3/4 999/ 358TS 12 S E B PD: k10302 LP 0.00 ft
TB 8.0 T1 9.5 2L/C 4.7 VA 1000 VE 1024 LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT

VMX= 4.5 FMX= 70 AMX= 149
EMX= 0.3 MEX= 137 FVP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: K10302

CALIBRATION FACTOR: .0716 mV/g

PAK (*5000): 358 DATE: 18 JAN 18

PDA OPERATOR: [Signature]

<-AT:PIEZORESISTIVE

OP: laine [ver:5.01]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By A.M.W. on 18 JAN 18 CRC Value CB00