

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

Pile Dynamics
2015-05-06 06:02FS —
10BN 131
SL 520/ 3440/ 99PJ:
PN: HOPBAR

TG F2

DPF

A 4

US

F 2

3.3

LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16810 ft/s
WC 17032 ft/sJC 0.40
FM 1.00
UM 1.00EA/C 30.3 Ks/ft
UN KIPS±0.1
FR 20000 MB 30DL -42
UT -1 IP 0.00
PK 1 TM-PEAKF1/2 500/ 213
F3/4 213/ 213
A1/2 999/ 999
A3/4 999/ 378TS 12
TB 8.0E B PD: k10303
T1 9.5 2L/C 4.7

VA 1000

UE 1024

LP 0.00 ft
LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT



<-AT:PIEZORESISTIVE

ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER: K10303

CALIBRATION FACTOR: .0756 mV/g

PAK (*5000): 378

DATE: 19JAN18

PDA OPERATOR: J.A.

OP: laine [ver:5.01]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By J.M.N. on 19JAN18 CRC Value 2600