

QBTA: ON [ALT-F1/BB=60]

File Dynamics, Inc.

TG F2 DPF

File Dynamics
2015-05-06 06:04FS — BN 135 PJ:
10 SL 520/ 3440/ 99 PN: HOPBARA 4 -- US
F 2 3.3LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16810 ft/s
WC 17032 ft/sJC 0.40
FM 1.00
UM 1.00EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 30DL -33
UT -1 IP 0.00
PK 1 TM-PEAKF1/2 500/ 213
F3/4 213/ 213
A1/2 999/ 999
A3/4 999/ 368TS 12 E B PD: k10304 LP 0.00 ft
TB 8.0 T1 9.5 2L/C 4.7 VA 1000 VE 1024 LI 1.0VMX= 4.4 FMX= 69 AMX= 139
EMX= 0.3 MEX= 135 FVP= 0.99

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT



ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER:

K10304

CALIBRATION FACTOR:

0.0736 mV/g

PAK (*5000):

368

DATE:

19 JAN 18

PDA OPERATOR:

[Signature]

<-AT:PIEZORESISTIVE

OP: laine [ver:5.01]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By X.M.W. on 19 JAN 18 CRC Value 4AB6