

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

TG F2 DPF

Pile Dynamics 2015-05-05 12:02		FS — 10	BN 106 SL 504/ 3440/ 2	PJ: PN: HOPBAR	A 4 -- US F 2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17032 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -42 UT -1 IP 0.00 PK 1 TM-PEAK					
F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 374		TS 12 TB 8.0	E B PD: k10305 T1 9.6 2L/C 4.7	UA 1000 UE 1024	LP 0.00 ft LI 1.0
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.3 FMX= 68 AMX= 139 EMX= 0.3 MEX= 133 FUP= 1.00			
ACCEPT		ACCELEROMETER CALIBRATION N.I.S.T. Traceable			
		SERIAL NUMBER: K10305			
		CALIBRATION FACTOR: .0748 MV/G			
		PAK (*5000): 374 DATE: 18 JAN 18			
PDA OPERATOR: Xa					
<-AT:PIEZORESISTIVE		OP: laine lver:5.011		AT:PIEZOELECTRIC->	

Smart Sensor

Smart Chip Programmed By R.M.W. on 18 JAN 18 CRC Value B2D7