

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

TG F2 DPF

Pile Dynamics 2015-05-05 12:01	FS — 10	BN 105 SL 502/ 3440/ 2	PJ: PN: HOPBAR	A 4 — US F 2 3.3
-----------------------------------	------------	---------------------------	-------------------	---------------------

LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16810 ft/s
WC 17032 ft/s

JC 0.40
FM 1.00
UM 1.00

EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 30

DL -41
UT -1 IP 0.00
PK 1 TM-PEAK

F1/2 500/ 213
F3/4 213/ 213
A1/2 999/ 999
A3/4 999/ 374



TS 12 E B PD: k10307 LP 0.00 ft
TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1024 LI 1.0

UMX= 4.5 FMX= 69 AMX= 149
EMX= 0.3 MEX= 135 FVP= 1.01

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT



ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER: K10307

CALIBRATION FACTOR: .0748 MV/G

PAK (*5000): 374

DATE: 18JAN18

PDA OPERATOR: JAW

<-AT:PIEZORESISTIVE

OP: laine [ver:5.01]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By J.M.W. on 18JAN18 CRC Value 007C