

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

TG F2 DPF

Pile Dynamics
2015-05-05 12:30FS —
10BN 116
SL 510/ 3440/ 99PJ:
PN: HOPBARA 4 -- US
F 2 3.3LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16810 ft/s
WC 17032 ft/sJC 0.40
FM 1.00
UM 1.00EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 30DL -41
VT -1 IP 0.00
PK 1 TM-PEAKF1/2 500/ 213
F3/4 213/ 213
A1/2 999/ 999
A3/4 999/ 368TS 12
TB 8.0E B PD: k10308
T1 9.6 2L/C 4.7

VA 1000

VE 1024

LP 0.00 ft
LI 1.0VMX= 4.7 FMX= 72 AMX= 149
EMX= 0.3 MEX= 141 FUP= 0.99

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT



ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER: K10308

CALIBRATION FACTOR: .0736 MV/G

PAK (*5000): 368

DATE: 18 JAN 18

PDA OPERATOR: [Signature]

<-AT:PIEZORESISTIVE

OP: laine [ver:5.01]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By J.M.W. on 18 JAN 18 CRC Value 4563