

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

TG F2 DPF

Pile Dynamics
2015-05-05 12:04FS —
10BN 110
SL 508/ 3440/ 2PJ:
PN: HOPBARA 4 — US
F 2 3.3LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16810 ft/s
WC 17032 ft/sJC 0.40
FM 1.00
UM 1.00EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 30DL -44
UT -1 IP 0.00
PK 1 TM-PEAKF1/2 500/ 213
F3/4 213/ 213
A1/2 999/ 999
A3/4 999/ 394TS 12 E B PD: k10309 LP 0.00 ft
TB 8.0 T1 9.6 2L/C 4.7 VA 1000 UE 1024 LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT

VMX= 4.5 FMX= 71 AMX= 149
EMX= 0.3 MEX= 139 FVP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: K10309

CALIBRATION FACTOR: .0788 MV/G

PAK (*5000): 394 DATE: 18 JAN 18

PDA OPERATOR: [Signature]

<-AT:PIEZORESISTIVE

OP: Iaine [ver:5.01]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By J.M.W. on 18 JAN 18 CRC Value 4190