

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

TG F2 DPF

Pile Dynamics 2015-05-06 05:58		FS — 10	BN 124 SL 514/ 3440/ 2	PJ: PN: HOPBAR	A 4 F 2	US 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17032 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -43 UT -1 IP 0.00 PK 1 TM-PEAK F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 368						
TS 12 TB 8.0		E B PD: k10310 T1 9.6 2L/C 4.7		UA 1000 UE 1024 LP 0.00 ft LI 1.0		
ACCEPT SQ-OFF FL-OFF PR-OFF ACCEPT 		VMX= 4.3 FMX= 67 AMX= 129 EMX= 0.3 MEX= 131 FVP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: K10310 CALIBRATION FACTOR: .0736 MV/G PAK (*5000): 368 DATE: 19JAN18 PDA OPERATOR: [Signature]				
←-AT:PIEZORESISTIVE		OP: laine [ver:5.01]		AT:PIEZOELECTRIC→		

Smart Sensor

Smart Chip Programmed By X.M.W. on 19JAN18 CRC Value 901B