

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

Pile Dynamics 2018-06-19 10:31		FS — 10	BN 4436 SL 1835/ 3440/ 2	PJ: PN: HOPBAR	TG F2 A 4 -- US F 2 3.3	DPF
LE 17.0 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 7312 ft/s						
JC 0.40 FM 1.00 VM 1.00						
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 90						
DL -40 UT -1 IP 0.00 PK 1 TM-PEAK						
F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 385						
TS 12 TB 8.0		E B PD: K10573 T1 9.6 2L/C 4.7 VA 1000 UE 1024 LP 0.00 ft LI 1.0				
ACCEPT SQ-OFF FL-OFF PR-OFF		UMX= 4.5 FMX= 69 AMX= 139 EMX= 0.3 MEX= 135 FVP= 1.00				
ACCEPT		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: K10573 CALIBRATION FACTOR: .077 mV/g PAK (*5000): 385 DATE: _____ PDA OPERATOR: [Signature]				
←-AT:PIEZORESISTIVE		OP: Iaine Iver:5.011		AT:PIEZOELECTRIC->		

Smart Sensor

Smart Chip Programmed By A.W. on _____ CRC Value 39FA