

File Dynamics		FS		BN 4937		PJ:		TG F2		DPF	
2018-06-28 10:38		10		SL 582/ 3440/ 99		PN: HOPBAR		A 4 -- US		F 2 3.3	
LE	17.0 ft										
AR	1.7 in2										
EM	30000 Ksi										
SP	0.492 K/ft3										
WS	16810 ft/s										
WC	7312 ft/s										
JC	0.40										
FM	1.00										
VM	1.00										
EA/C 30.3 Ks/ft											
UN KIPS±0.1											
FR 20000 MB 90											
DL	-40										
UT	-1 IP 0.00										
PK	1 TM-PEAK										
F1/2	500/ 213										
F3/4	213/ 213										
A1/2	999/ 999										
A3/4	999/ 374	TS 12	E B	PD: K10578	LP 0.00 ft						
		TB 8.0	T1 9.4	2L/C 4.7	UA 1000	VE 1024	LI 1.0				
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.5 FMX= 69 AMX= 120 EMX= 0.3 MEX= 135 FVP= 1.00									
ACCEPT		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: <u>K10578</u> CALIBRATION FACTOR: <u>.0748 mV/g</u> PAK (*5000): <u>374</u> DATE: <u>19JULY18</u> PDA OPERATOR: <u>[Signature]</u>									
<-AT:PIEZORESISTIVE		OP: laine [ver:5.01]				>AT:PIEZOELECTRIC->					

Smart Sensor

Smart Chip Programmed By A.W. on 19JULY18 CRC Value B1B6