

File Dynamics, Inc.				TG F2	DPF
File Dynamics 2018-08-20 13:38		FS — 10	BN 7642 SL 1300/ 3440/ 99	PJ: PN: HOPBAR	A 4 -- US F 2 3.3
LE 17.0 ft AR 1.7 in2 EM 30000 Ks1 SP 0.492 K/ft3 WS 16810 ft/s WC 7312 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 90 DL -36 UT -1 IP 0.00 PK 1 TM-PEAK F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 370					
TS 12 TB 8.0		E B PD: K10581 T1 9.4 2L/C 4.7 UA 1000 UE 1024 LP 0.00 ft LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF ACCEPT 		UMX= 4.0 FMX= 61 AMX= 120 EMX= 0.2 MEX= 119 FUP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: K10581 CALIBRATION FACTOR: 0.074 MV/G PAK (*5000): 370 DATE: PDA OPERATOR: <i>[Signature]</i>			
<-AT:PIEZORESISTIVE		OP: LAINE Iver:5.011		AT:PIEZOELECTRIC->	

OCT 1 1 2018

Smart Sensor

Smart Chip Programmed By J. W. on _____ CRC Value F068