

Pile Dynamics		File Dynamics, Inc.		TG F2	DPF
2018-08-20 13:35	FS 10	BN 7638	PJ: SL 1300/ 3440/ 99	A 4	-- US
LE 17.0 ft			PN: HOPBAR	F 2	3.3
AR 1.7 in2					
EM 30000 Ksi					
SP 0.492 K/ft3					
WS 16810 ft/s					
WC 7312 ft/s					
JC 0.40					
FM 1.00					
UM 1.00					
EA/C 30.3 Ks/ft					
UN KIPS*0.1					
FR 20000 MB 90					
DL -41					
UT -1 IP 0.00					
PK 1 TM-PEAK					
F1/2 500/ 213					
F3/4 213/ 213					
A1/2 999/ 999					
A3/4 999/ 370					
TS 12		E B	PD: K10582	LP 0.00 ft	
TB 8.0		T1 9.4	2L/C 4.7	UA 1000	UE 1024 LI 1.0
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.4 FMX= 68 AMX= 149 EMX= 0.3 MEX= 133 FVP= 1.01			
ACCEPT		ACCELEROMETER CALIBRATION N.I.S.T. Traceable			
		SERIAL NUMBER: K10582			
		CALIBRATION FACTOR: .074 mV/g			
		PAK (*5000): 370 DATE:			
		PDA OPERATOR: <i>[Signature]</i>			
←AT:PIEZORESISTIVE		OP: LAINE [ver:5.01]		AT:PIEZOELECTRIC→	

OCT 11 2018

Smart Sensor

Smart Chip Programmed By A.W. on _____ CRC Value BB17