


Pile Dynamics, Inc.		TG F2	DPF
Pile Dynamics 2018-08-20 13:41	FS — 10	BN 7647 SL 1300/ 3440/ 99	PJ: PN: HOPBAR
LE 17.0 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 7312 ft/s			A 4 -- US F 2 3.3
JC 0.40 FM 1.00 VM 1.00			
EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB-90			
DL -41 UT -1 IP 0.00 PK 1 TM-PEAK			
F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 378	TS 12 TB 8.0	E B PD: K10583 T1 9.4 2L/C 4.7	LP 0.00 ft LI 1.0
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.2 FMX= 64 AMX= 129 EMX= 0.3 MEX= 125 FUP= 1.01	
ACCEPT		ACCELEROMETER CALIBRATION N.I.S.T. Traceable	
		SERIAL NUMBER: K10583	
		CALIBRATION FACTOR: .0756 MV/G	
		PAK (<5000): 378 DATE: DEC 03 2018	
		PDA OPERATOR: 	
←-AT-PIEZORESISTIVE		AT-PIEZOELECTRIC→	
		OP: LAINE Iver:5.011	

Smart Sensor

Smart Chip Programmed By A.W. on _____ CRC Value A7F1