

Pile Dynamics, Inc.		TG F2	DPF
Pile Dynamics 2018-08-20 13:32		FS — BN 7631 10 SL 1300/ 3440/ 99	PJ: PN: HOPBAR A 4 -- US F 2 3.3
LE 17.0 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 7312 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 90 DL -43 UT -1 IP 0.00 PK 1 TM-PEAK F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 376			
TS 12 TB 8.0 T1 9.5 E B PD: K10584 2L/C 4.7 VA 1000 VE 1024 LP 0.00 ft LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF ACCEPT 		VMX= 4.5 FMX= 69 AMX= 159 EMX= 0.3 MEX= 135 FUP= 0.99 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: K10584 CALIBRATION FACTOR: .0752 MV/G PAK (*5000): 376 DATE DEC 19 2018 PDA OPERATOR: <i>[Signature]</i>	
<-AT:PIEZORESISTIVE		OP: LAINE [ver:5.01] AT:PIEZOELECTRIC->	

Smart Sensor

Smart Chip Programmed By A.W. on _____ CRC Value 3F2F