


File Dynamics		FS		BN 7629		PJ:		TG F2		DPF	
2018-08-20 13:30		10		SL 1300/ 3440/ 99		PN: HOPBAR		A 4 -- US		F 2 3.3	
LE 17.0 ft											
AR 1.7 in2											
EM 30000 Ksi											
SP 0.492 K/ft3											
WS 16810 ft/s											
WC 7312 ft/s											
JC 0.40											
FM 1.00											
VM 1.00											
EA/C 30.3 Ks/ft											
UN KIPS*0.1											
FR 20000 MB 90											
DL -40											
UT -1 IP 0.00											
PK 1 TM-PEAK											
F1/2 500/ 213											
F3/4 213/ 213											
A1/2 999/ 999											
A3/4 999/ 370											
TS 12											
TB 8.0											
E B PD: K10585											
T1 9.5											
2L/C 4.7											
UA 1000											
UE 1024											
LP 0.00 ft											
LI 1.0											
ACCEPT SQ-OFF FL-OFF PR-OFF											
ACCEPT											
											
ACCELEROMETER CALIBRATION											
N.I.S.T. Traceable											
SERIAL NUMBER: K10585											
CALIBRATION FACTOR: .074 MV/G											
PAK (*5000): 370											
DATE:											
PDA OPERATOR: 											
<-AT:PIEZORESISTIVE											
OP: LAINE [ver:5.01]											
AT:PIEZOELECTRIC->											

Smart Sensor

Smart Chip Programmed By A. W. on NOV 13 2018 CRC Value 05B0