

Pile Dynamics		FS —		BN 6093		PJ:		TG F2		DPF	
2018-07-24 08:36		10		SL 925/ 3440/ 2		PN: HOPBAR		A 4 -- US		F 2 3.3	
LE	17.0 ft										
AR	1.7 in2										
EM	30000 Ksi										
SP	0.492 K/ft3										
WS	16810 ft/s										
WC	7312 ft/s										
JC	0.40										
FM	1.00										
UM	1.00										
EA/C 30.3 Ks/ft											
UN KIPS*0.1											
FR 20000 MB 90											
DL	-44										
UT	-1 IP 0.00										
PK	1 TM-PEAK										
F1/2	500/ 213										
F3/4	213/ 213										
A1/2	999/ 999										
A3/4	999/ 358										
TS 12		E B		PD: K10587		LP 0.00 ft					
TB 8.0		T1 9.6		2L/C 4.7		VA 1000		UE 1024		LI 1.0	
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.6 FMX= 72 AMX= 179 EMX= 0.3 MEX= 141 FVP= 0.99									
ACCEPT		ACCELEROMETER CALIBRATION N.I.S.T. Traceable									
		SERIAL NUMBER: <u>K10587</u> CALIBRATION FACTOR: <u>.0716 mV/g</u> PAK (*5000): <u>358</u> DATE: _____ PDA OPERATOR: <u>[Signature]</u>									
<-AT:PIEZORESISTIVE		OP: laine [ver:5.01]						AT:PIEZOELECTRIC->			

Smart Sensor

Smart Chip Programmed By A.W. on SEP 27 2018 CRC Value 9400