

File Dynamics, Inc.		TG F2	DPF
File Dynamics 2018-07-24 08:34 LE 17.0 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 7312 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 90 DL -40 UT -1 IP 0.00 PK 1 TM-PEAK F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 388	FS — 10 BN 6089 SL 921/ 3440/ 2 PJ: PN: HOPBAR	A 4 -- US F 2 3.3	
TS 12 TB 8.0		E B PD: K10588 T1 9.6 2L/C 4.7 VA 1000 UE 1024 LP 0.00 ft LI 1.0	
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.4 FMX= 68 AMX= 149 EMX= 0.3 MEX= 133 FVP= 1.00	
ACCEPT 		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: K10588 CALIBRATION FACTOR: -0.776 MV/G PAK (*5000): 388 DATE: PDA OPERATOR: <i>[Signature]</i>	
<-AT:PIEZORESTITIVE		OP: Iaine [ver:5.01] AT:PIEZOELECTRIC->	

Smart Sensor

Smart Chip Programmed By A.W. on OCT 04 2018 CRC Value 82C0