

File Dynamics		FS —		BN 6100		PJ:		TG F2		DPF	
2018-07-24 08:39		10		SL 927/ 3440/ 99		PN: HOPBAR		A 4 -- US		F 2 3.3	
LE 17.0 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 7312 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 90 DL -44 UT -1 IP 0.00 PK 1 TM-PEAK F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 408											
		TS 12 E B PD: K10589 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1024 LI 1.0									
		VMX= 5.0 FMX= 77 AMX= 189 EMX= 0.4 MEX= 150 FVP= 0.98									
ACCEPT SQ-OFF FL-OFF PR-OFF ACCEPT 		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: K10589 CALIBRATION FACTOR: .0816 mV/g PAK (*5000): 408 DATE: PDA OPERATOR: <i>[Signature]</i>									
<-AT:PIEZORESISTIVE		OP: laine lver:5.011						AT:PIEZOELECTRIC->			

Smart Sensor

Smart Chip Programmed By A. W. on OCT 04 2018 CRC Value FD6C