

File Dynamics		FS —		BN 6104		PJ:		TG F2		DPF	
2018-07-24 08:41		10		SL 927/ 3440/ 99		PN: HOPBAR		A 4 -- US		F 2 3.3	
LE 17.0 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 7312 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 90 DL -44 UT -1 IP 0.00 PK 1 TM-PEAK F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 400											
		TS 12 E B PD: K10590 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1024 LI 1.0									
		VMX= 4.3 FMX= 67 AMX= 149 EMX= 0.3 MEX= 131 FVP= 1.00									
ACCEPT SQ-OFF FL-OFF PR-OFF		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: K10590 CALIBRATION FACTOR: .08 mV/g PAK (*5000): 400 DATE: _____ PDA OPERATOR: <i>[Signature]</i>									
ACCEPT 											
←-AT:PIEZORESISTIVE		OP: laine [ver:5.01]						AT:PIEZOELECTRIC->			

Smart Sensor

Smart Chip Programmed By Z. W. on OCT 04 2018 CRC Value F0AB