

File Dynamics, Inc.				TG F2	DPF
File Dynamics 2018-06-29 09:25		FS — 10	BN 4946 SL 592/ 3440/ 99	PJ: PN: HOPBAR	A 4 -- US F 2 3.3
LE 17.0 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 7312 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 90 DL -42 UT -1 IP 0.00 PK 1 TM-PEAK F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 414					
TS 12 TB 8.0		E B PD: K10591 T1 9.4 2L/C 4.7 VA 1000 UE 1024 LP 0.00 ft LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.5 FMX= 69 AMX= 120 EMX= 0.3 MEX= 135 FVP= 1.00			
ACCEPT 		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: K10591 CALIBRATION FACTOR: .0828 mV/g PAK (*5000): 414 DATE: _____ PDA OPERATOR: [Signature]			
<-AT:PIEZORESISTIVE		OP: laine [ver:5.01]		AT:PIEZOELECTRIC->	

Smart Sensor

Smart Chip Programmed By A.W. on _____ CRC Value 00A6