

File Dynamics, Inc.				TG F2	DPF
File Dynamics 2018-06-29 09:23		FS — 10	BN 4944 SL 590/ 3440/ 2	PJ: PN: HOPBAR	A 4 -- US F 2 3.3
LE 17.0 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 7312 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 90 DL -44 UT -1 IP 0.00 PK 1 TM-PEAK F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 382		TS 12 E B PD: K10592 LP 0.00 ft TB 8.0 T1 9.4 2L/C 4.7 UA 1000 UE 1024 LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF ACCEPT 		VMX= 4.5 FMX= 70 AMX= 129 EMX= 0.3 MEX= 137 FVP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: K10592 CALIBRATION FACTOR: .0764 mV/g PAK (*5000): 382 DATE: PDA OPERATOR: <i>[Signature]</i>			
<-AT:PIEZORESISTIVE		OP: laine [ver:5.01]		AT:PIEZOELECTRIC->	

Smart Sensor

Smart Chip Programmed By A.W. on _____ CRC Value 104C