

File Dynamics, Inc.				TG F2	DPF
File Dynamics 2018-08-22 13:03		FS — 10	BN 7833 SL 1346/ 3440/ 2	PJ: PN: HOPBAR	A 4 -- US F 2 3.3
LE 17.0 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 7312 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 90 DL -37 UT -1 IP 0.00 PK 1 TM-PEAK F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 340		TS 12 E B PD: K10594 LP 0.00 ft TB 8.0 T1 9.4 2L/C 4.7 UA 1000 UE 1024 LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF ACCEPT 		VMX= 4.3 FMX= 65 AMX= 139 EMX= 0.3 MEX= 127 FVP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: K10594 CALIBRATION FACTOR: .068 MV/G PAK (*5000): 340 DATE: PDA OPERATOR: <i>[Signature]</i>			
←-AT:PIEZORESISTIVE		OP: LAINE [ver:5.01]		AT:PIEZOELECTRIC-→	

Smart Sensor

Smart Chip Programmed By J.W. on NOV 13 2018 CRC Value 7904