

Pile Dynamics, Inc.				TG F2	DPF
Pile Dynamics 2018-08-13 07:03		FS — 10	BN 7123 SL 1162/ 3440/ 99	PJ: PN: HOPBAR	A 4 -- US F 2 3.3
LE 17.0 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 7312 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB 90 DL -39 UT -1 IP 0.00 PK 1 TM-PEAK F1/2 500/ 213 F3/4 213/ 213 A1/2 999/ 999 A3/4 999/ 405					
		TS 12 TB 8.0	E B PD: K10595 T1 9.5 2L/C 4.7	VA 1000 UE 1024	LP 0.00 ft LI 1.0
		UMX= 4.3 FMX= 66 AMX= 120 EMX= 0.3 MEX= 129 FVP= 1.00			
ACCEPT SQ-OFF FL-OFF PR-OFF ACCEPT 		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: K10595 CALIBRATION FACTOR: .081 MV/G PAK (*5000): 405 DATE: _____ PDA OPERATOR: <i>[Signature]</i>			
<-AT:PIEZORESISTIVE		OP: LAINE [ver:5.01]		AT:PIEZOELECTRIC->	

Smart Sensor

Smart Chip Programmed By Z.W. on SEP 27 2018 CRC Value 82 EA