

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

TG F2 DPF

Pile Dynamics
1999-03-11 04:06FS —
10BN 807
SL 871/ 3440/ 99PJ:
PN: HOPBARA 4 -- US
F 2 3.3LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16815 ft/s
WC 16851 ft/sJC 0.40
FM 1.00
UM 1.00EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 90DL -42
UT -1 IP 0.00
PK 1 TM-PEAKF1/2 500/ 213
F3/4 213/ 213
A1/2 999/ 999
A3/4 999/ 495TS 12 E B PD: EMPR406 LP 0.00 ft
TB 8.0 T1 9.2 2L/C 4.7 VA 1000 UE 1024 LI 1.0VMX= 5.2 FMX= 84 AMX= 149
EMX= 0.4 MEX= 164 FVP= 1.00

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT



ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER:

EMPR406

CALIBRATION FACTOR:

0.099 m/g

PAK (*5000):

495

DATE:

08-7-2024

PDA OPERATOR:

Will

<-AT:PIEZORESISTIVE

OP: WILL Iver:5.011

AT:PIEZOELECTRIC->

Smart Sensor

Programmed By: WJCRC Value C149