

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

TG F2 DPF

Pile Dynamics
1999-03-11 04:20FS —
10BN 820
SL 877/ 3440/ 2PJ:
PN: HOPBARA 4 -- US
F 2 3.3LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16815 ft/s
WC 16851 ft/sJC 0.40
FM 1.00
VM 1.00EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 90DL -44
UT -1 IP 0.00
PK 1 TM-PEAKF1/2 500/ 213
F3/4 213/ 213
A1/2 999/ 999
A3/4 999/ 470TS 12
TB 8.0E B PD: EMPR408
T1 9.2 2L/C 4.7VA 1000 UE 1024 LP 0.00 ft
LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT

UMX= 5.7 FMX= 89 AMX= 159
EMX= 0.5 MEX= 174 FVP= 0.98

ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER:

EMPR408

CALIBRATION FACTOR:

0.094 m/s

PAK (*5000):

470

DATE: 08-7-2024

PDA OPERATOR:

Will

<-AT:PIEZORESISTIVE

OP: WILL [ver:5.01]

[AT:PIEZOELECTRIC->

Smart Sensor

Programmed By: WJ

CRC Value E427

