

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

TG F2 DPF

Pile Dynamics
1999-03-11 04:37FS —
10BN 844
SL 881/ 3440/ 99PJ:
PN: HOPBARA 4 -- US
F 2 3.3LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16815 ft/s
WC 16000 ft/sJC 0.40
FM 1.00
UM 1.00EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 90DL -50
UT -1 IP 0.00
PK 1 TM-PEAKF1/2 500/ 213
F3/4 213/ 213
A1/2 999/ 999
A3/4 999/ 460TS 12
TB 8.0E B PD: EMP410
T1 8.9 2L/C 4.9 VA 1000LP 0.00 ft
LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT

VMX= 5.3 FMX= 81 AMX= 139
EMX= 0.4 MEX= 158 FVP= 0.98

ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER: EMP410

CALIBRATION FACTOR: 0.092 m/g

PAK (*5000): 460

DATE: 08-7-2024

PDA OPERATOR: WJH

<-AT:PIEZORESISTIVE

OP: WILL [ver:5.01]

AT:PIEZOELECTRIC->

Smart Sensor

Programmed By: WJ

CRC Value B68A

