

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

TG F2 DPF

Pile Dynamics
1999-03-12 01:18FS — BN 911 PJ:
10 SL 921/ 3440/ 99 PN: HOPBARA 4 -- US
F 2 3.3LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16815 ft/s
WC 17032 ft/sJC 0.40
FM 1.00
UM 1.00EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 90DL -45
UT -1 IP 0.00
PK 1 TM-PEAKF1/2 500/ 213
F3/4 213/ 213
A1/2 999/ 999
A3/4 999/ 489TS 12 E B PD: EMPR416 LP 0.00 ft
TB 8.0 T1 9.2 2L/C 4.7 VA 1000 UE 1024 LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT

UMX= 5.7 FMX= 87 AMX= 159
EMX= 0.5 MEX= 170 FUP= 0.98

ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER:

EMPR416

CALIBRATION FACTOR:

.0978 m/s²

PAK (*5000):

489

DATE: 08-08-24

PDA OPERATOR:

Will

JK

<-AT:PIEZORESISTIVE

OP: WILL [ver:5.01]

AT:PIEZOELECTRIC->

Smart Sensor

Programmed By: WJ

CRC Value 8312

