

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

TG F2 DPF

Pile Dynamics
1999-03-13 01:26FS — BN 949 PJ:
10 SL 951/ 3440/ 99 PN: HOPBARA 4 -- US
F 2 3.3LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16815 ft/s
WC 16330 ft/sJC 0.40
FM 1.00
VM 1.00EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 90DL -47
UT -1 IP 0.00
PK 1 TM-PEAKF1/2 500/ 213
F3/4 213/ 213
A1/2 999/ 999
A3/4 999/ 475TS 12 E B PD: EMPR421 LP 0.00 ft
TB 8.0 T1 9.0 2L/C 4.8 VA 1000 VE 1024 LI 1.0VMX= 5.5 FMX= 86 AMX= 139
EMX= 0.5 MEX= 168 FUP= 0.99

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT



ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: EMPR421

CALIBRATION FACTOR: 0.095 m/g

PAK (*5000): 475 DATE: 08-09-24

PDA OPERATOR: Will

<-AT:PIEZORESISTIVE

OP: WILL [ver:5.01]

AT:PIEZOELECTRIC->

Smart Sensor

Programmed By: WJ

CRC Value 8C57

