

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

TG F2 DPF

File Dynamics 1999-03-13 01:34		FS — 10	BN 953 SL 955/ 3440/ 2	PJ: PN: HOPBAR	A 4 F 2	-- US 3.3
LE 39.6 ft	AR 1.7 in2	EM 30000 Ksi	SP 0.492 K/ft3	WS 16815 ft/s	WC 16500 ft/s	
JC 0.40	FM 1.00	UM 1.00				
EA/C 30.3 Ks/ft						
UN KIPS*0.1						
FR 20000 MB 90						
DL -51	UT -1	IP 0.00				
PK 1	TM-PEAK					
F1/2 500/ 213	F3/4 213/ 213	A1/2 999/ 999	A3/4 999/ 450	TS 12	TB 8.0	
		E B	PD: EMPR422	2L/C 4.8	VA 1000	UE 1024
		LP 0.00 ft	LI 1.0			

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 5.6 FMX= 87 AMX= 149
EMX= 0.4 MEX= 170 FVP= 0.98

ACCEPT 	ACCELEROMETER CALIBRATION	N.I.S.T. Traceable
	SERIAL NUMBER:	EMPR422
	CALIBRATION FACTOR:	0.09 mV/g
	PAK (*5000):	450
PDA OPERATOR:		WJH PL

<-AT:PIEZORESISTIVE

OP: WILL [ver:5.01]

[AT:PIEZOELECTRIC->

Smart Sensor

Programmed By: WJHCRC Value 1155