

QBTA: ON [ALT-F1/BB=60]


Pile Dynamics, Inc.

TG F2 DPF

Pile Dynamics
1999-03-16 01:30FS —
10BN 987
SL 971/ 3440/ 99PJ:
PN: HOPBARA 4 -- US
F 2 3.3LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16815 ft/s
WC 16851 ft/sJC 0.40
FM 1.00
UM 1.00EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 90DL -48
UT -1 IP 0.00
PK 1 TM-PEAKF1/2 500/ 213
F3/4 213/ 213
A1/2 999/ 999
A3/4 999/ 430TS 12 E B PD: EMPR426 LP 0.00 ft
TB 8.0 T1 8.9 2L/C 4.7 UA 1000 UE 1024 LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

ACCEPT

UMX= 5.8 FMX= 89 AMX= 149
EMX= 0.5 MEX= 174 FVP= 0.97

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: EMPR 426

CALIBRATION FACTOR: 0.086 m/s²

PAK (*5000): 430 DATE: 08-12-2024

PDA OPERATOR: Will

<-AT:PIEZORESISTIVE

OP: WILL [ver:5.01]

[AT:PIEZOELECTRIC->

Smart Sensor

Programmed By: WJS

CRC Value 7887

