

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 06-Nov-13 14:10		FS — 10	BN 1082 SL 231/ 3440/ 99	PJ: PN: HOPBAR	TG F2 A2 F2	-- US 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30						
DL -30 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 1160		TS 12 TB 8.0	B T1 9.6	PD: 10084-075 2L/C 4.7	VA 1000 UE 1022	LP 0.00 ft LI 1.0

	UMX= 4.0 FMX= 62 AMX= 129 EMX= 0.2 MEX= 121 FUP= 1.00
	ACCEPT SQ-OFF FL-OFF PR-OFF
ACCELEROMETER CALIBRATION N.I.S.T. Traceable	SERIAL NUMBER: <u>10084</u>
CALIBRATION FACTOR: <u>1160 G/v</u>	PAK (#5000): _____ DATE: <u>6-Nov-13</u>
PDA OPERATOR: <u>Erik Laver</u>	OP: erik [ver:4.05]
<-AT:PIEZORESISTIVE	AT:PIEZOELECTRIC->

contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916