

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 21-Oct-13 09:56		FS — 10	BN 715 SL 161/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -31 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1180					
		TS 12 TB 8.0	B PD: 10085-075 T1 9.4 2L/C 4.7	VA 1000 UE 1022	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

VMX= 3.9 FMX= 60 AMX= 149
 EMX= 0.2 MEX= 117 FVP= 1.00

ACCELEROMETER CALIBRATION

N.I.S.T. Traceable

SERIAL NUMBER: 10085

CALIBRATION FACTOR: 1180 G/v

PAK (*5000):

DATE: 21-OCT-13

PDA OPERATOR:

<-AT:PIEZORESISTIVE

OP: ALEX [ver:4.05]

AT:PIEZOELECTRIC->