

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 21-Oct-13 08:45		FS — 10	BN 553 SL 155/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -40 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1155					
TS 12 TB 8.0		B PD: 10089-075 T1 9.5 2L/C 4.7 VA 1000 LP 0.00 ft LI 1.0			

ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 3.9 FMX= 60 AMX= 139 EMX= 0.2 MEX= 117 FVP= 1.00	
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable	
SERIAL NUMBER: 10089		CALIBRATION FACTOR: 1155 G/v	
PAK (x5000):		DATE: 21-OCT-13	
PDA OPERATOR:		OP: ALEX [ver:4.05]	
<-AT:PIEZORESISTIVE		AT:PIEZOELECTRIC->	

contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916