

QBTB: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 21-Oct-13 09:53		FS — 10	BN 704 SL 161/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN ~~KIPSS~~ 0.1 FR 20000 MB 30 DL -34 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1155		TS 12 B PD: 10090-075 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 VA 1000 VE 1022 LI 1.0			
ACCEPT SQ-OFF FL-OFF PR-OFF		UMX= 3.9 FMX= 62 AMX= 149 EMX= 0.2 MEX= 121 FUP= 1.00			
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 10090 CALIBRATION FACTOR: 1155 Gw DATE: 21-OCT-13			
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		PDA OPERATOR: <i>Alex</i> OP: ALEX [ver:4.051]			
<-AT:PIEZORESISTIVE		[AT:PIEZOELECTRIC->			