

Pile Dynamics 21-Oct-13 09:05		FS — 10	BN 611 SL 155/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -26 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1150		TS 12 B PD: 10093-075 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 VA 1000 VE 1022 LI 1.0			

ACCEPT SQ-OFF FL-OFF PR-OFF
 VMX= 4.1 FMX= 64 AMX= 149
 EMX= 0.3 MEX= 125 FUP= 0.99



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10093

CALIBRATION FACTOR: 1150 G/v

PAK (*5000): DATE: 21-OCT-13

PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: ALEX [ver:4.05]

AT:PIEZOELECTRIC->