

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 08-Nov-13 11:52		FS — 10	BN 1205 SL 236/ 3440/ 99	PJ: PN: HOPBAR	TG F2 A2 F2	-- US 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30						
DL -29 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 1200						
		TS 12 TB 8.0	B PD: 10110-075 T1 9.6	2L/C 4.7 UA 1000	LP 0.00 ft LI 1.0	UE 1022

ACCEPT SQ-OFF FL-OFF PR-OFF
 VMX= 4.0 FMX= 62 AMX= 149
 EMX= 0.2 MEX= 121 FUP= 0.99



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10110

CALIBRATION FACTOR: 1200 G/v

PAK (*5000): DATE: 8-Nov-13

PDA OPERATOR: Erik S. [Signature]

<-AT:PIEZORESISTIVE

OP: erik [ver:4.05]

[AT:PIEZOELECTRIC->