

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 08-Nov-13 11:56		FS — 10	BN 1212 SL 237/ 3440/ 99	PJ: PN: HOPBAR	TG F2 A2 F2	-- US 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB 30						
DL -25 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 1175		TS 12 TB 8.0	B T1 9.4	PD: 10111-075 2L/C 4.7	VA 1000 UE 1022	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF
VMX= 3.9 FMX= 60 AMX= 139
EMX= 0.3 MEX= 117 FUP= 0.97



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10111

CALIBRATION FACTOR: 1175 G/v

PAK (*5000): DATE: 8-Nov-13

PDA OPERATOR: Erik S. [Signature]

<-AT:PIEZORESISTIVE

OP: erik [ver:4.05]

[AT:PIEZOELECTRIC->