

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 08-Nov-13 11:13		FS — 10	BN 1110 SL 236/ 3440/ 99	PJ: PN: HOPBAR	TG F2 — US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s							
JC 0.40 FM 1.00 UM 1.00							
EA/C 30.3 Ks/ft UN KIPS:0.1 FR 20000 MB 30							
DL -39 UT -1 PK 1 TM-PEAK							
F1 500 F2 213 A1 999 A2 1140		TS 12 TB 8.0	B T1 9.4	PD: 10112-075 2L/C 4.7	UA 1000 UE 1022	LP 0.00 ft LI 1.0	

ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.0 FMX= 62 AMX= 129 EMX= 0.2 MEX= 121 FVP= 1.01
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		SERIAL NUMBER: <u>10112</u> CALIBRATION FACTOR: <u>1140 G/v</u> PAK (*5000): _____ DATE: <u>8-Nov-13</u> PDA OPERATOR: <u>Erik Smith</u>
<-AT:PIEZORESISTIVE		OP: erik [ver:4.05] AT:PIEZOELECTRIC >