

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 02-Aug-14 05:09		FS — 10	BN 120 SL 142/ 3440/ 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -32 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1135		TS 12 B PD: 10115-075 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 VA 1000 VE 1022 LI 1.0			

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

VMX= 4.2 FMX= 66 AMX= 139
 EMX= 0.3 MEX= 129 FVP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10115

CALIBRATION FACTOR: 1135%

PAK-(*5000):

DATE: 2 AUG 14

PDA OPERATOR: M. Wright

OP: Jaine Iyer: 4.051

A: PIEZOELECTRIC->

<-AT:PIEZORESISTIVE