

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 08-Jan-14 09:52		FS — 10	BN 90 SL 128/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -40 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1160					
		TS 12 TB 8.0	B PD: 10120-075 T1 9.3 2L/C 4.7	VA 200 VE 1022	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF
 VMX= 3.9 FMX= 61 AMX= 120
 EMX= 0.2 MEX= 119 FUP= 1.01



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 10120
 CALIBRATION FACTOR: 1160 G/v
 PAK (*5000): DATE: 8-Jan-14
 PDA OPERATOR: Erik S.

<-AT:PIEZORESISTIVE

OP: erik lver:4.05]

[AT:PIEZOELECTRIC->