

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 07-Oct-14 03:17		FS —	BN 1984	PJ:	TG F2 -- US
		10	SL 452/ 3440/ 99	PN: HOPBAR	A2 F2 3.3
LE 39.6 ft					
AR 1.7 in2					
EM 30000 Ksi					
SP 0.492 K/ft3					
WS 16810 ft/s					
WC 16862 ft/s					
JC 0.40					
FM 1.00					
UM 1.00					
EA/C 30.3 Ks/ft					
UN KIPS*0.1					
FR 20000 MB 30					
DL -41					
UT -1					
PK 1	TM-PEAK				
F1 500					
F2 213					
A1 999					
A2 1190					
TS 12		B	PD: 10125-075	LP 0.00 ft	
TB 8.0		T1 9.5	2L/C 4.7	VA 1000	UE 1022 LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

<-AT:PIEZORESISTIVE

VMX= 4.2 FMX= 65 AMX= 139
EMX= 0.3 MEX= 127 FVP= 1.01

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10125

CALIBRATION FACTOR: 1190 %

PAK-<*5000>: DATE: 7 OCT 14

PDA OPERATOR: M. Wong

OP: Iaine Iver:4.051

>AT:PIEZOELECTRIC->