

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 21-Apr-15 01:29		FS — 10	BN 3702 SL 1548/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3	
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS 30.1 FR 20000 MB 30						
DL -40. UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 1180		TS 12 TB 8.0	E B T1 9.6	PD: 10129-075 2L/C 4.7	UA 1000 VE 1022	LP 0.00 ft LI 1.0
ACCEPT SQ-OFF FL-OFF PR-OFF		VMX= 4.3 FMX= 66 AMX= 129 EMX= 0.3 MEX= 129 FUP= 0.99				
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable				
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		SERIAL NUMBER: 10129 CALIBRATION FACTOR: 1180 %				
←-AT:PIEZORESISTIVE		PAK (*5000): DATE: 24 APR 15 PDA OPERATOR: J. M. W. W. W. OP: laine [ver:4.05]				

AT:PIEZOELECTRIC